



# Wheel Paint

## Product Description

VHT® Wheel Paint provides a great finish and real protection for all standard and custom wheels. Every day wheels take a beating both on and off the road. Salt, sand, brake dust, and rocks severely damage the appearance and protection of the wheel surface. This unique product resists chipping, cracking and fading, while protecting the wheel surface from oxidation. Product is ok up until 250° F or 121° C.

## Product Characteristics

**Colors:** Aluminum, Satin Black, Clear Coat, Chevy Rally Silver, Gloss Black, Ford Argent Silver, & Graphite

**Finish:** Satin and Gloss

## Properties

**Product Weight:** 6.06 lb/gal

**Flash Point:** Propellant < 0° F

## Coating System

VHT provides a multi-high performance coating system for the ultimate in protection and quality. The system includes surface preparation, prime, paint, and clear coat.

**Prep** SP445 Prep Spray

**Prime** SP148 Engine Primer

**Coat** SPxxx Wheel Paint Color

**Clear** SP184 Clear Coat

## Uses

Rims

Surfaces:

- Metal

## Application

*Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. Use grease and wax remover to clean surface. Lightly sand surface with 320-grit sand paper or Red Scotch Brite pad. Wipe surface down with grease and wax remover again.*

Mask-off surrounding areas to protect from overspray. Use at temperatures between 60° F (16° C) and 95° F (35° C) and when humidity is less than 60%.

Shake can vigorously until mixing ball moves freely and 10 seconds after each minute of use. If bare metal is exposed apply VHT Prime Coat primer or equivalent first. To spray, hold can parallel 8 to 10 inches from the surface to be painted and use in an even, sweeping motion. Apply 2 light coats, followed by 1 medium wet coat. Apply all coats in one hour allowing 10 minutes between each coat. For additional coats after 1 hour, wait seven days for paint to cure. Dries to the touch in 20 minutes and can be handled in three hours. Covers approximately 12-14 square feet. For added protection apply VHT SP184 clear coat.

The EZ Touch™ Nozzle results in 50% less finger fatigue than a standard nozzle, as well as allowing greater coverage and less overspray.

**No extra steps for curing required.**

## Packaging

**Fill Weight:** 11.25 oz

**Per Case:** 6 cans

**Case Weight:** 5.82 lbs

**Cases/Pallet:** 156

**Units/Pallet:** 936 cans